

KP25S

Dual 15 Inch High-Power Passive Subwoofer

Professional Series

Key Features:

- ▶ Dual 15" high-power and long-excursion cone driver for extended low-frequency reproduction
- Sophisticated acoustic cabinet design for high efficiency
- ▶ High sensitivity with low power compression
- ▶ Low profile and compact
- ► Enclosure features a combination of 18mm and 25mm multi-ply birch construction with attractive durable finish



Applications:

► Karaoke sound reinforcement

The KP25S is a dual 15" compact, high power subwoofer for Karaoke sound reproduction. It utilizes two JBL long excursion woofers. The high-performance driver, in conjunction with the optimized enclosure design, provides the best low frequency performance to size ratio. The KP25S subwoofer is designed to provide low-frequency reinforcement for the entire JBL KP Series family of full-range loudspeakers.

The loudspeaker enclosure is constructed of high-quality multi-ply birch and features a sophisticated design utilizing a combination of 18mm and 25mm plywood with internal bracing, eliminating cabinet resonance at extreme sound pressure levels. The KP25S is finished in a high-quality, durable paint.

Specifications:

System:		
	System Type:	Dual 15", bass-reflex
	Frequency Range (-10 dB)1:	32 Hz – 150 Hz
	Frequency Response (±3 dB)1:	40 Hz – 150 Hz
	System Sensitivity (1W @ 1m)1:	97 dB
	Nominal Impedance:	4 ohms
	Maximum SPL:	127 dB (133 dB peak)
	Power Rating ² : (Continuous/Program/Peak)	1000 W/2000 W/4000 W
Physical:		
	Dimensions (H x W x D):	450mm x 1100mm x 560mm
		(17.72 in x 43.31 in x 22.05 in)
	Net Weight:	53 Kg (116.85 lbs)
	LF Driver:	2 x 15" woofer
	Input Connectors:	2 x Neutrik® Speakon® NL4MP
	Enclosure:	Rectangular, 18 mm and 25 mm, multi-ply
		birch


¹ Full space (4π) conditions

JBL continually engages in research related to product improvement. Some materials, production methods and design refinements are introduced into existing products without notice as a routine expression of that philosophy. For this reason, any current JBL product may differ in some respect from its published description, but will always equal or exceed the original design specifications unless otherwise stated.

² IEC standard, pink noise with 6dB crest factor for 2 hours.


► KP25S Dual 15 Inch High-Power Passive Subwoofer


Frequency Response and Impedance:





Dimensions:

Dimensions in mm (inch)











JBL Professional 8500 Balboa Boulevard, P.O. Box 2200 Northridge, California 91329 U.S.A. © Copyright 2013 JBL Professional www.jblpro.com